



UNIVERSAL HEATSHRINK / RESIN COMBINATION JOINT FOR 7.2-12kV CABLES



- Suits 3 Core Xlpe/Pilc/Picas Cables or Transition combinations Complete with Tapered range taking Mechanical Connectors, High Impact Shell and Twin Pack Polyurethane Resin
- Offers the superior insulation benefits of Heatshrink combined with Resin for environmental protection
- Designed and tested to BS7888 and Cenelec HD 628 S1 and HD 629 S1, ASTA test report available

Shrink Polymer Systems now offer from stock, a Universal Heatshrink Joint complete with Mechanical Shearbolt Connectors, High Impact Shell, Twin Pack Polyurethane Resin and full Earthing accessories for Xlpe, Pilc and Picas Cable combinations.

The standard Joint comes complete with modules that enable all Cable types and sizes to be catered for. This is ideal for Distributors who wish to cut down their stock levels and Contractors that cannot be sure of the exact Cables they will encounter on site.

Note:- Due to the modular nature of the Joint, if cable type is known, modules can be omitted at ordering stage to reduce initial price.

NON CENTRALISED TYPE CONNECTORS CURRENTLY USED BY COMPETITORS



SPS JOINT HAS TAPERED PROFILE WITH CONDUCTORS CENTRALISED

PART NUMBER	CONDUCTOR SIZE	CABLE TYPES
SPUJ 12U 35-70-3	35-70mm ²	XLPE/PILC/PICAS
SPUJ 12U 95-185-3	95-185mm ²	XLPE/PILC/PICAS
SPUJ 12U 185-300-3	185-300mm ²	XLPE/PILC/PICAS
SPUJ 12X 35-70-3	35-70mm ²	XLPE
SPUJ 12X 95-185-3	95-185mm ²	XLPE
SPUJ 12X 185-300-3	185-300mm ²	XLPE
SPUJ 12PX 35-70-3	35-70mm ²	TRANSITION
SPUJ 12PX 95-185-3	95-185mm ²	TRANSITION
SPUJ 12PX 185-300-3	185-300mm ²	TRANSITION
SPUJ 12P 35-70-3	35-70mm ²	PILC/PICAS
SPUJ 12P 95-185-3	95-185mm ²	PILC/PICAS
SPUJ 12P 185-300-3	185-300mm ²	PILC/PICAS

Note:- Items 1-3 are the Universal type, items 4-12 have only the required modules.